

C401730: Verify that resumption Token contains tenantId

Type	Priority	Estimate	References
Other	Critical	None	MODOAIPMH-516
Release	Execution Type	Test Group	Dev Team
R2 2023 Poppy	Manual	Draft	Firebird
Bug Created	Multi-Tenant	User Journey	
No	No	No	

Preconditions

1. "Record source" is set to "Source record storage and Inventory" on the "Settings"> "OAI-PMH">"Behavior"-> "Record source" = "Source record storage and Inventory" 2. "Max records per response" is set to "30" on the "Settings"> "OAI-PMH">"Technical"-> "Max records per response" = "30" 3. The system must have at least 31 records that were updated in the past, not in current date 4. User has experience using the FOLIO API. You can see documentation by the link: <https://wiki.folio.org/display/FOLIOtips/Working+with+FOLIO+APIs> User has "Postman" app (or any similar API-client; will be used to send request to interact with FOLIO's API).

Steps

1	<p><b>From the browser tab:</b></p> <p>Go to "Inventory" app =&gt; "Instance" toggle is selected on the "Search &amp; filter" pane =&gt; Expand "Date updated" accordion =&gt; Select dates in the past and click "Apply" button to search for the date range returning sufficient number of records (see Preconditions # 3)</p> <p>NOTE: search for the number of records not less than 31 and no more than 100</p>	<ul style="list-style-type: none"><li>The "Inventory" pane is being populated with Instances updated within the specified range</li><li>In "Inventory" pane "&lt;count of record&gt; records found" text displays required number of records</li></ul>
2	<p><b>From "Postman" app:</b></p> <p>Send "GET" request to the endpoint with following parameters:</p> <p><b>{{url}}/oai/records?verb=ListIdentifiers&amp;metadataPrefix=marc21&amp;from=&lt;datefrom&gt;&amp;until=&lt;dateto&gt;</b></p> <p>NOTE: &lt;date_from&gt; and &lt;date_to&gt; are the dates from the date range Step 1 - should be in the format: yyyy-mm-dd (for example: 2023-07-06)</p>	<ul style="list-style-type: none"><li>Responses contain number of records inline with configured max records per response (e.g. 30)</li><li>All but the last response contain <b>resumptionToken element</b></li><li>Harvesting succeeds without errors and all inventory and SRS instances are harvested</li></ul>
3	<p>Copy &lt;resumptionToken&gt; value to the clipboard</p>	<p>&lt;resumptionToken&gt; value is copied to the clipboard</p>
4	<p>Decode resumptionToken value (Base64 Decode)</p>	<p>Resumption token includes parameters:</p> <ul style="list-style-type: none"><li>metadataPrefix</li><li>from</li><li>until</li><li><b>tenantId</b></li><li>nextInstancePkValue</li></ul>



- offset
- requestId
- completeListSize
- nextRecordId
- expirationDate

E.g. "metadataPrefix=marc21&from=2023-07-06&until=2023-07-06&tenantId=diku&nextInstancePkValue=1570&offset=50&requestId=72195348-8e4b-4eba-b432-32d2362de8c7&completeListSize=268&nextRecordId=34a3c9fd-7adb-4e58-94ad-0bf25e7a1272&expirationDate=2023-07-07T08:25:27Z"